Fiberglass Lagging Cloth - Style 2025/9383 with Acrylic

TECHNICAL INFO

Style 2025/9383 glass lagging fabric with 2% acrylic coating is designed to replace asbestos. It is used for removable blankets, pipe wrapping, turbine blankets, fittings, flange covers and engine exhaust pipes.

The cloth has been heat treated so that large percentages of organic binders on the fabric have been removed. This enhances the hand and weave setting characteristics. This style fabric has been designed for continuous use at temperatures up to 1000°F. Meets MIL-C- 20079.

Physical Specifications

Weight (oz./sq.yd.): 18.5 Oz. Sq. Yd. +/- 10%

Thickness: .028" +/- 10%

Thread Count: 20 x 14

Tensile Warp: 300 lbs./inch

Tensile Fill: 150 lbs./inch

Weave: Plain

Temperature Resistance: Up to 1000°F (540°C)

Acrylic Coating: 2%



Revised 0514

For more information on GLT Products, please visit us online at www.gltproducts.com or call toll-free at 1-800-874-1748.



HEADQUARTERS:

6810 Cochran Road | Solon OH 44139 | 440.914.1122 | 440.914.1133 Fax | 1.800.874.1748

DISTRIBUTION CENTERS:

Ohio: Texas: California:

6810 Cochran Road | Solon OH 44139 | 440.914.1122 8905 Market Street | Houston, TX 77029 | 1.800.874.1748 North Carolina: 501 West Camel Street | Greensboro, NC 27401 | 1.800.551.9760 4113 Gold River Lane | Stockton, CA 95215 | 1.800.833.4500 Ontario, Canada: 55 Milburn Road | Hamilton, ON L8E 3C4 | 1.800.874.1748