

CAN YOUR REGULAR URETHANE FOAM DO THIS?



TremGlaze® Flex Foam provides a high-performance thermal and acoustical barrier around windows and doors. Gain peace of mind as this flexible foam helps alleviate concerns of a comprised seal caused by window movement from wind loads or temperature changes. TremGlaze Flex remains flexible after cure with an industry-leading movement range of +/-15%.

TremGlaze Flex Foam is part of the T3 Building Solutions System which provides a three-level solution to manage air flow, control moisture and provide thermal resistance around residential windows and doors.



FEATURES & BENEFITS

- Industry-leading movement range of +/-15% (Movement Accommodation Factor of 30%)
- CFC-free and can be applied over a wide temperature range, making it a reliable, four-season solution
- Minimal expanding/low pressure so windows won't bow or warp
- Non-rigid composition is highly flexible and won't crack
- Closed cell so it won't absorb water
- Can trim or cut in 45 minutes

DOCUMENTED, TESTED PERFORMANCE

FLEXIBILITY Test: Even after 1000 testing cycles over 166 hours, where the TremGlaze Flex Foam joint was stretched and compressed to 1/8 or 15%, the foam seal remained reliable.

AAMA 812: TremGlaze Flex Foam had a maximum pressure build of 0.633 psi which indicates low potential for bowing or warping of windows and doors.

ASTM D2842-06: After 96 hours of immersion, TremGlaze Flex Foam had a .03% water absorption which indicates there is little or no absorption.



TREMCO PU APPLICATOR GUNS

PU PRO APPLICATOR

- Part Number: 001798MG501
- Heavy-duty gun that provides durability and total control
- All-aluminum construction
- Lightweight and compact
- Corrosion and wear-resistant
- Ergonomically-designed for comfort during extended use
- Spring trigger for accurate flow control



PU CONTRACTOR APPLICATOR

- Part Number: 001701MG501
- Plastic and metal combination
- Lightweight and compact
- Economic choice
- Spring trigger for accurate flow control
- Standard screw thread design for bead size adjustment and flow control



PU STANDARD APPLICATOR

- Part Number: 001798PG501
- All-plastic design
- Highly cost-effective, "disposable" choice
- Standard screw thread design for bead size adjustment and flow control



PU FOAM CLEANER

- Part Number: 001922GC501
- Packaging: 12 per case
- Pre-pressurized in an aerosol spray can
- Dispenses in the upright or inverted position
- Evaporates quickly
- Can be fitted directly to a PU foam gun, or used as a handheld aerosol can



PU FOAM APPLICATOR TIPS

- Part Number: 001400 501
- Replacement tips for PU applicator guns
- Color: White
- Packaging: 50/box



3735 Green Road
Beachwood, OH 44122
216.292.5000 • 800.321.7906

1451 Jacobson Avenue
Ashland, OH 44805
800.321.6357

220 Wicksteed Avenue
Toronto, ON M4H 1G7
416.421.3300 • 800.363.3213



TREMCO
Residential Window Business