

Product Description

TremGlaze® U1600 is a high-performance, low modulus, one-component, moisture curing hybrid sealant.

TremGlaze U1600 is a durable, flexible hybrid sealant that offers excellent performance in back-bedding and in the installation of windows and doors.

Features and Benefits

- Compatible with self-cleaning glass applications
- Aggressive adhesion to a variety of window substrates including wood, vinyl, aluminum and glass
- Easy to apply with conventional hand caulking and air gunning equipment
- Excellent long-term weather resistance
- UV Stable

Availability

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

Packaging

10.1-oz (300-mL) cartridges: Almond, Andersen Canvas, Andersen Sandstone, Andersen Terratone, Andersen White, Beige, Black, Bronze, Polar White, Sandstone, TG Beige, White

20-oz (600 ml) Sausages: Black, Bronze, Sandstone, White

50-gal (189)-L) Drum: White

Colors

See Packaging for color available by size.

Special colors available upon request. Minimum order requirements exist for special colors.

Applicable Standards

- Conforms to AAMA 802.3-92 Type I
- AAMA 802.3-92 Type II
- AAMA 808.3-92
- U.S. Federal Specification TT-S- 00230C, Class A, Type II
- Canadian Standard CAN/CGSB-19.13-M87
- ASTM C920, Type S, Grade NS, Class 35, Use NT, M, A and O

Limitations

- Do not apply over wet or contaminated surfaces.
- Not for use as an insulated glass sealant.

Application

Product dispensed from drums can be applied using standard one-part pumping equipment. TremGlaze U1600 cartridges are easy to apply with conventional hand-caulking and air gunning equipment. Fill joint completely to a proper width-to-depth ratio and tool.

Warranty

Tremco warrants its Products to be free of defects in material but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or refund the purchase price of the quantity of Tremco Products proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

| PROPERTY | TEST METHOD | TYPICAL VALUES |
|---|---|--|
| Rheological Properties at 40 and 122° F (4.4 and 50° C) | <Rheological Properties at 40 and 122° F (4.4 and <50° C) | 0, None |
| Extrusion Rate | ASTM C920 | 15 |
| Hardness Properties | ASTM C920 | 25 |
| Weight Loss | ASTM C920 | Passes (<2%) |
| Skin Time | ASTM C920 | 30 to 90 min |
| Tack-Free Time | ASTM C920 | 3 to 4 hr |
| Stain & Color Change | ASTM C920 | None |
| Adhesion-in-Peel | ASTM C920 | Concrete 18 to 22 pli, Aluminum 20 to 25 pli, No Adhesion Loss |
| Effects of Accelerated Weathering | ASTM C920 | Passes |
| Movement Capability | ASTM C920 | ±35% |

0518/TGU1600DS-ST

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

| Tremco Commercial Sealants & Waterproofing | | | |
|--|--|---|--|
| 3735 Green Rd Beachwood OH 44122 216.292.5000 / 800.321.7906 | 1451 Jacobson Ave Ashland OH 44805 419.289.2050 / 800.321.6357 | 220 Wicksteed Ave Toronto ON M4H1G7 416.421.3300 / 800.363.3213 | 1445 Rue de Coulomb Boucherville QC J4B 7L8 514.521.9555 |

