



Ideal Tape® 888, Double Coated PET Tape

PRODUCT DESIGN

Ideal Tape 888 is a double coated polyester film tape with a high tack pressure sensitive adhesive system.

APPLICATION

Ideal Tape 888 is designed for a variety of automotive, insulation, and leather goods manufacturing applications. Use 888 for automotive gaskets, seals and trim, for SSL tape for pipe covering fabrication and PVC fittings, and as a general purpose double sided bonding tape in footwear manufacturing.

PERFORMANCE FEATURES

- Extreme temperature resistance
- High tack adhesive system bonds to a wide variety of surfaces, including paper, plastic, and cloth
- Resistant to oils and plasticizers

PHYSICAL PROPERTIES	VALUE	TEST METHOD
Tape Thickness	3.1 mils (0.08 mm)	PSTC 133
Peel Adhesion	70 oz/in (19 N/25 mm)	PSTC 101
Shear Strength	>7 days	PSTC 107
Service Temp.	-30°F to 220°F (-34°C to 104°C)	

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry and free of grease, oil or other contaminants. NS 031023

Ideal Tape Co., Inc.

1400 Middlesex Street, Lowell, MA 01851

Toll Free: 800-229-9148 • WWW.IDEALTAPE.COM