



# Cold Seal™ 788

## PRODUCT DESIGN

Cold Seal 788 is an aluminum foil coated with a cold weather acrylic adhesive on a paper release liner.

## APPLICATION

Cold Seal 788 is designed for sealing and seaming duct board, duct wrap, and metal ducts.

## PERFORMANCE FEATURES

- High performance cold weather acrylic adhesive system provides a durable, long-term bond
- Dead soft aluminum foil backing blends into basic facing patterns and conforms to irregular surfaces such as FSK facings
- Zero perm and creates a closed system
- Release liner provides easy removal for efficient application on the job site
- Coast Guard Approval - USCG COA Number 164.112/161/0

PHYSICAL PROPERTIES	VALUE	TEST METHOD
Backing Thickness	1.6 mils (0.04mm)	PSTC-133
Tape Thickness	3.5 mils (0.09 mm)	PSTC-133
Peel Adhesion	90 oz/in (25 N/25 mm)	PSTC-101
Tensile Strength	20 lb/in (88 N/25 mm)	PSTC-131
Minimum Application Temp.	-5°F (-20°C)	
Operating Temp. Range	-35°F to 250°F (-37°C to 121°C)	
Surface Burning Characteristics	Flame Spread: 0 Smoke Developed: 0	UL 723 ASTM E84

## CLASSIFICATIONS

UL Classified, UL 723 Rated, USCG COA Number 164.112/161/0

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 24 months from the date of manufacture. Application surfaces should be clean, dry and free of grease, oil or other contaminants. NS 030923



**Ideal Tape Co., Inc.**

1400 Middlesex Street, Lowell, MA 01851

Toll Free: 800-229-9148 • [WWW.IDEALTAPE.COM](http://WWW.IDEALTAPE.COM)