

411 Reinforced Strapping

Product Design

Ideal Tape 411 is a fiberglass reinforced polypropylene film tape with a performance pressure sensitive adhesive system.

Application

Ideal Tape 411 was designed for bundling, palletizing, and other packaging applications where high impact strength and adhesion are required.

Performance Features

(BOPP) Biaxially Oriented Polypropylene film and fiberglass reinforced backing provides solid bond and impact resistance

Performance adhesive system

| Physical Properties | Value |
|---------------------|------------------------|
| Backing Type | ВОРР |
| Thickness | 4.2 mils (0.11mm) |
| Adhesion to Steel | 50 oz/in (14 N/25mm) |
| Tensile Strength | 175 lb/in (766 N/25mm) |
| Elongation % | 4 |
| Color | Natural |

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. 01/2016 Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry and free of grease, oil or other contaminants.

CV411/0119

