



**469**  
**UL 723 Rated**

## Product Design

Ideal Tape 469 is a standard grade polyethylene coated cloth tape with an aggressive rubber pressure sensitive adhesive.

## Application

Ideal Tape 469 is a general use duct tape that is suitable for a variety of applications. Common uses include general purpose packaging, bundling and securing on the job site in abatement and waterproofing projects.

## Performance Features

- ☑ **Aggressive adhesive system** performs on a range of materials
- ☑ **High conformability** provides ease of use on rigid surfaces
- ☑ **UL 723 rated**

Physical Properties	Value
Backing Type	Polyethylene Coated Cloth
Total Thickness	9 mils (0.23mm)
Adhesion to Steel	50 oz/in (14 N/25mm)
Tensile Strength	20 lb/in (88 N/25mm)
Elongation %	18
Adhesive System	Rubber
Application Temp. Range	50°F to 200°F
Color	Silver, Black

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. 01/2016 Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry and free of grease, oil or other contaminants.

CV469/0119

