



888

Double Coated Tape

Product Design

Ideal Tape 888 is a double sided polyester film tape with a high tack pressure sensitive adhesive system.

Application

Ideal Tape 888 is designed for a variety of applications including corrugated and paper splicing, name and label plate mounting, display fabrication and engraving, and carpet hold down.

Performance Features

- ✓ Easy to use—fast, simple and clean application
- ✓ High tack adhesive system is UV and chemical resistant
- ✓ High quick stick offers fast and secure bond on different types of surfaces

Physical Properties	Value
Backing Type	Polyester film
Total Thickness	3.75 mils (0.10mm)
Adhesion to Steel	50 oz/in (14 N/25mm)
Tensile Strength	18 lb/in (79 N/25mm)
Elongation %	5
Adhesive System	Acrylic
Color	Clear

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. 01/2016 Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry and free of grease, oil or other contaminants.

MK888/0119

