

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

Product Identifier 0263S1NL

CARBOCRYLIC 3359 Revision Date: 02/14/2019 **Product Name:**

> Monocomponent industrial coating - Industrial use.

Supercedes Date:

10/23/2018

1.2 Relevant identified uses of the substance or mixture and uses

advised against

1.3 Details of the supplier of the safety data sheet

> Carboline Company Manufacturer:

2150 Schuetz Road St. Louis, MO USA 63146

Regulatory / Technical Information: Contact Carboline Technical Services at

1-800-848-4645

Schlereth, Ken - ehs@stoncor.com **Datasheet Produced by:**

CHEMTREC 1-800-424-9300 (Inside US) 1.4 Emergency telephone number:

CHEMTREC +1 703 5273887 (Outside US)

HEALTH - Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification

2.1 Classification of the substance or mixture

Reproductive Toxicity, category 1B

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

DIBUTYL PHTHALATE

HAZARD STATEMENTS

Reproductive Toxicity, category 1B

PRECAUTION PHRASES

H360-1B May damage fertility or the unborn child.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P284 Wear respiratory protection.

P308+P313 IF exposed or concerned: Get medical advice/attention

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	Chemical Name	<u>%</u>
13463-67-7	TITANIUM DIOXIDE	10 - <25
111-77-3	DM GLYCOL ETHER	2.5 - <10
112-34-5	GLYCOL ETHER SOLVENT	1.0 - <2.5
84-74-2	DIBUTYL PHTHALATE	1.0 - <2.5
1333-86-4	CARBON BLACK	1.0 - <2.5
25322-68-3	POLYETHYLENE GLYCOL	1.0 - <2.5

CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
13463-67-7			0
111-77-3	GHS08	H361	0
112-34-5	GHS07	H319	0
84-74-2	GHS08-GHS09	H360-400	0
1333-86-4			0
25322-68-3	GHS07	H319	0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Evacuate personnel to safe areas. The product is not flammable. Use NIOSH approved respiratory protection.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Avoid breathing vapors, mist or gas. Wash thoroughly after handling. PROTECTION AND HYGIENE MEASURES: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks. Do not freeze.

STORAGE CONDITIONS: Do not freeze. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	CAS-No.	ACGIH TWA ACGIH STE	L ACGIH Ceiling
TITANIUM DIOXIDE	13463-67-7	10 MGM3 10 MGM3 N/E	N/E
DM GLYCOL ETHER	111-77-3	N/E N/E	N/E
GLYCOL ETHER SOLVENT	112-34-5	10 PPM N/E	N/E

DIBUTYL PHTHALATE	84-74-2	5 MGM3	N/E	N/E
CARBON BLACK	1333-86-4	3 MGM3	N/E	N/E
POLYETHYLENE GLYCOL	25322-68-3	N/E	N/E	N/E

<u>Name</u>	CAS-No.	OSHA PEL	OSHA STEL
TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E
DM GLYCOL ETHER	111-77-3	N/E	N/E
GLYCOL ETHER SOLVENT	112-34-5	N/E	N/E
DIBUTYL PHTHALATE	84-74-2	5.0 MG/M3	N/E
CARBON BLACK	1333-86-4	3.5 MG/M3	N/E
POLYETHYLENE GLYCOL	25322-68-3	N/E	N/E

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Viscous Liquid, Various Colors

Physical State Liquid
Odor Ammonia

 Odor threshold
 N/D

 pH
 N/D

 Melting point / freezing point (°C)
 N/D

Boiling point/range 212 F (100 C) - 644 F (340 C)

Flash Point 248F (120C)

Evaporation rate Slower Than Ether

Flammability (solid, gas)

Not determined

Upper/lower flammability or explosive 0.9 - 24.6

limits

Vapour Pressure, mmHg N/D

Vapour density Heavier than Air
Relative density Not determined

Solubility in / Miscibility with water N/D

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity Unknown

Explosive properties Not determined

Oxidising properties Not determined

9.2 Other information

VOC Content g/l: 60

Specific Gravity (g/cm3) app. 1.16

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks. Do not freeze.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: N/D Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Unknown

Mutagenicity: Unknown

Toxicity for reproduction: Reproductive toxicity, category 1B

STOT-single exposure: Unknown

STOT-repeated exposure: Unknown

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available	No Information	No Information
111-77-3	DM GLYCOL ETHER	7000 mg/kg, oral, rat		Not Available	0.000	0.000
112-34-5	GLYCOL ETHER SOLVENT	3305 mg/kg, oral, rat	2700 mg/kg, dermal, rabbit	Not Available	0.000	0.000
1333-86-4	CARBON BLACK	8000 mg/kg oral, rat	Not Available	Not Available		
25322-68-3	POLYETHYLENE GLYCOL	Not Available		Not Available	0.000	0.000

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

Unknown

Unknown

Unknown

Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: Unknown

CAS-No.	<u>Chemical Name</u>	EC50 48hr	IC50 72hr	LC50 96hr
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
111-77-3	DM GLYCOL ETHER	No information	No information	No information
112-34-5	GLYCOL ETHER SOLVENT	>100 mg/l (Daphnia magna)	>100 mg/l (Algae)	1300 mg/l (Fish)
84-74-2	DIBUTYL PHTHALATE	No information	No information	No information
1333-86-4	CARBON BLACK	No information	No information	No information
25322-68-3	POLYETHYLENE GLYCOL	No information	No information	No information

13. Disposal Considerations

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Transport Information

14.1	UN number	None

14.2 UN proper shipping name Not Regulated

Technical name N/A None 14.3 Transport hazard class(es) N/A Subsidiary shipping hazard 14.4 Packing group N/A Unknown 14.5 Environmental hazards 14.6 Special precautions for user Unknown EmS-No.: Unknown Unknown

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

15. Regulatory Information

Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Reproductive toxicity

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.DM GLYCOL ETHER111-77-3GLYCOL ETHER SOLVENT112-34-5DIBUTYL PHTHALATE84-74-2

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.SODIUM NITRITE7632-00-0

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.WATER7732-18-5ACRYLIC RESINTRADE SECRETYELLOW PIGMENT31837-42-0COLOR PIGMENT5567-15-7

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name CAS-No. WATER 7732-18-5 **ACRYLIC RESIN** TRADE SECRET YELLOW PIGMENT 31837-42-0 **COLOR PIGMENT** 5567-15-7 **COLOR PIGMENT** 36888-99-0 **AZO PIGMENT** 2786-76-7 **IRON OXIDE** 1309-37-1 **COLOR PIGMENT** 15793-73-4 **IRON OXIDE** 1332-37-2 YELLOW IRON OXIDE 51274-00-1 **AZO PIGMENT** 82199-12-0

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.