

FOSTER 30-36 AF 802258PM

SAFETY DATA SHEET

REVISION DATE: 03-13-2017 SUPERSEDES: 11-21-2016

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: FOSTER 30-36 AF

PRODUCT DESCRIPTION: Coating
INTENDED USE: Coating
PRODUCT IDENTIFIER: 802258PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street Aurora, IL 60504 Phone: 1-800-552-6225

> Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Symbols:





GHS Signal Word: Warning

GHS Classification: Skin Sensitisation Category 1; Hazardous to the aquatic environment - Acute Category

2; Hazardous to the aquatic environment - Chronic Category 2

GHS Hazard Phrases:

GHS Precautions: Safety Precautions:

Precautions:

should not be allowed out of the workplace. Avoid release to the environment. Wear

protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get

medical advice/attention. Wash contaminated clothing before reuse. Collect spillage.

May cause an allergic skin reaction.; Toxic to aquatic life with long lasting effects.

Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulation for hazardous wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT	Classification	Note
Calcium carbonate	471-34-1	10 - 30		* (see below)
Kaolin clay	1332-58-7	5 - 10		* (see below)
Iodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1	Aquatic Acute 1; H400 Acute Tox. 4; H332 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335, H336	

FOSTER 30-36 AF 802258PM

SAFETY DATA SHEET

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: There is a possibility of pressure buildup in closed containers

when heated. Water spray may be used to cool the containers.

SPECIAL FIRE FIGHTING INSTRUCTIONS:

Persons exposed to products of combustion should wear self-

Persons exposed to products of combustion should wear selfcontained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide Chlorine containing gases

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the

quantity of the spill, the area in which the spill occurred.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated

area.



FOSTER 30-36 AF 802258PM

SAFETY DATA SHEET

Storage: Store in a cool, dry place. Protect from freezing. Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Calcium carbonate	* (see below)	No data available.	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Kaolin clay	* (see below)	2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Titanium dioxide	* (see below)	10 mg/m3 TWA	15 mg/m3 TWA (total dust)

^{*}This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

ENGINEERING CONTROL METHODS:

VENTILATION: General room ventilation might be required under normal conditions

of use.

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur.

GLOVES: Nitrile

RESPIRATORY PROTECTION: No respiratory protection required under normal conditions of use.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid COLOR: White ODOR: Mild Solvent ODOR THRESHOLD: Not established Not established FREEZING/MELTING POINT (deg. C): Not established BOILING POINT (deg. C): Not established FLASH POINT: Non flammable **EVAPORATION RATE:** Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

VAPOR DENSITY:

Not established

Not established

WEIGHT PER GALLON (lbs.): 10.50 SPECIFIC GRAVITY: 1.250

SOLUBILITY: Not established



FOSTER 30-36 AF 802258PM

SAFETY DATA SHEET

OCTANOL/WATER COEFFICIENT:

AUTOIGNITION TEMPERATURE:

DECOMPOSITION TEMPERATURE:

VISCOSITY:

Not established

Not established

Not established

Not established

SOLIDS (% by weight): 51.3

VOC, weight percent

VOC, U.S. EPA Method 24, less water and exempt

Not determined
17g/liter of material

solvents (analytically determined)

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Chlorine containing gases Carbon monoxide, carbon

dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation :No irritation hazard in normal industrial use.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that is suspected of causing cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available. Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: No data available. Target organs potentially affected by exposure: Kidneys Liver Lungs

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Liver disease, Kidney disease, Lung disease

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available. PERSISTENCE: No data available. BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

FOSTER 30-36 AF 802258PM

SAFETY DATA SHEET

Component:	Ecotoxicity values:
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-
	through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50
	Lepomis macrochirus: >0.1 mg/L [flow-through]
	Acute Toxicity (Daphnia): Not established
	Acute Toxicity (Algae): Not established
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-
	through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50
	Lepomis macrochirus: >0.1 mg/L [flow-through]
	Acute Toxicity (Daphnia): Not established
	Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT: NOT REGULATED

IATA: UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID,

N.O.S. (C14-C17 CHLORINATED PARAFFINS), 9, PGIII, MARINE POLLUTANT (PACKAGES <5 L NOT REGULATED, IATA 4.4, SP

A197).

IMDG: UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (C14-C17 CHLORINATED PARAFFIN), 9, III, MARINE

POLLUTANT (PACKAGES <5 L NOT REGULATED, IMDG 3.3 SP 969)

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt

from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met

AUSTRALIA AICS: This product contains a component that is not on the Australian

Inventory (AICS).

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical

Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg_request@hbfuller.com to request an export review.

FEDERAL REPORTING

FOSTER 30-36 AF 802258PM

SAFETY DATA SHEET

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
3-Iodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Titanium dioxide	(Carcinogen)	13463-67-7	1 - 5
Quartz	(Carcinogen)	14808-60-7	0.1 - 1
Methyl isobutyl ketone	(Carcinogen)	108-10-1	0.1 - 1
Formaldehyde	(Carcinogen)	50-00-0	0.001 - 0.01
Acetaldehyde	(Carcinogen)	75-07-0	0.001 - 0.01
Methanol	(Developmental toxin)	67-56-1	0.1 - 1
Methyl isobutyl ketone	(Developmental toxin)	108-10-1	0.1 - 1

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 03-13-2017

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of





FOSTER 30-36 AF 802258PM

SAFETY DATA SHEET

the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.