

SAFETY DATA SHEET

REVISION DATE: 04-15-2020

SUPERSEDES: 04-14-2017

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER**PRODUCT INFORMATION**

PRODUCT: FOSTER 81-33
PRODUCT DESCRIPTION: Adhesive
INTENDED USE: Adhesive
PRODUCT IDENTIFIER: 802391PM

COMPANY INFORMATION

H.B. Fuller Company
1200 Willow Lake Boulevard
Vadnais Heights, MN 55110
Telephone: 888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION**GHS Hazard
Symbols:****GHS Signal Word:**

Danger

GHS**Classification:**

Respiratory Sensitisation Category 1; Skin Sensitisation Category 1; Germ Cell Mutagenicity Category 1B; Carcinogenicity Category 1A; Hazardous to the aquatic environment - Acute Category 1; Reproductive Toxicity Category 2; Hazardous to the aquatic environment - Chronic Category 2; Flammable Liquid Category 3; Additional category for effects on or via lactation

GHS Hazard**Phrases:**

Flammable liquid and vapour.; May cause an allergic skin reaction.; May cause allergy or asthma symptoms or breathing difficulties if inhaled.; May cause genetic defects.; May cause cancer.; Suspected of damaging fertility or the unborn child.; May cause harm to breast-fed children.; Very toxic to aquatic life.; Toxic to aquatic life with long lasting effects.

GHS Precautions:**Safety****Precautions:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection.

**First Aid
Measures:**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: If breathing is difficult, remove victim to fresh air and

SAFETY DATA SHEET

keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish. Collect spillage.

Storage: Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulation for chemical wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
Chlorinated paraffin: CAS:63449-39-8	63449-39-8	5 - 10	Aquatic Acute 1; H400	
Trimethylbenzene, 1,2,4-	95-63-6	1 - 5	Aquatic Chronic 2; H411 Acute Tox. 4; H332 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335, H336	
Xylene	1330-20-7	1 - 5	Acute Tox. 4; H312 Acute Tox. 4; H332 Flam. Liq. 3; H226 Skin Irrit. 2; H315	
Crystalline silica	14808-60-7	0.1 - 1	Carc. 1A; H350 STOT RE 1; H372	* (see below)
Titanium dioxide	13463-67-7	0.1 - 1	Carc. 2; H351	* (see below)
Cristobalite	14464-46-1	0.1 - 1	Acute Tox. 4; H332 Carc. 2; H351 STOT RE 1; H372	* (see below)
Hindered phenolic antioxidant	119-47-1	0.1 - 1	Aquatic Chronic 4; H413 Repr. 2; H361	
Stoddard solvent	8052-41-3	0.1 - 1	Asp. Tox. 1; H304 Carc. 1B; H350 Muta. 1B; H340	
Calcium 2-ethylhexanoate	136-51-6	0.1 - 1	Aquatic Chronic 2; H411 Acute Tox. 4; H332 Acute Tox. 4; H302 Flam. Liq. 3; H226 Resp. Sens. 1; H334 Skin Sens. 1; H317	

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

SAFETY DATA SHEET

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Vapors are heavier than air and can travel to a source of ignition and flash back.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide Chlorine containing gases Metal fumes Nitrogen containing gases

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.
METHODS FOR CLEAN-UP:	Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling:	Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Keep away from heat, sparks and flame. Wash thoroughly after handling. Keep container closed. Emptied container retains vapor and product residue. Observe all labeled precautions until container is cleaned. Drums of this material should be grounded when pouring. DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.
Storage:	Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep container closed.

SAFETY DATA SHEET

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Kaolin clay	* (see below)	2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
Calcium carbonate	* (see below)	No data available.	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
Inorganic Filler	* (see below)	3 mg/m ³ TWA (respirable particulate matter)	Not established
Zinc oxide		2 mg/m ³ TWA (respirable particulate matter) 10 mg/m ³ STEL (respirable particulate matter)	5 mg/m ³ TWA (fume); 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
Xylene		100 ppm TWA 150 ppm STEL	100 ppm TWA; 435 mg/m ³ TWA
Crystalline silica	* (see below)	0.025 mg/m ³ TWA (respirable particulate matter)	((250)/(%SiO ₂ + 5) mppcf TWA (respirable)); ((10)/(%SiO ₂ + 2) mg/m ³ TWA (respirable)); ((30)/(%SiO ₂ + 2) mg/m ³ TWA (total dust))
Titanium dioxide	* (see below)	10 mg/m ³ TWA	15 mg/m ³ TWA (total dust)
Cristobalite	* (see below)	0.025 mg/m ³ TWA (respirable particulate matter)	50 µg/m ³ TWA (listed under Respirable crystalline silica)
Stoddard solvent		100 ppm TWA	500 ppm TWA; 2900 mg/m ³ TWA
Ethylbenzene		20 ppm TWA	100 ppm TWA; 435 mg/m ³ TWA

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

ENGINEERING CONTROL METHODS:

VENTILATION:	General room ventilation might be required under normal conditions of use.
EYE PROTECTION:	Wear safety glasses when handling this product.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur.
GLOVES:	Nitrile
RESPIRATORY PROTECTION:	No respiratory protection required under normal conditions of use. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

SAFETY DATA SHEET

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
COLOR:	Off-white
ODOR:	Solvent
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	43°C; 109°F TCC
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
WEIGHT PER GALLON (lbs.):	13.10
SPECIFIC GRAVITY:	1.590
SOLUBILITY:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	80.0
VOC, weight percent	Not determined
VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined)	300g/liter of material

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Strong oxidizing agents
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide Chlorine containing gases Metal fumes Nitrogen containing gases

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Kaolin clay	Oral LD50 Rat > 5,000 mg/kg Dermal LD50 Rat > 5,000.00 mg/kg
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg
Trimethylbenzene, 1,2,4-	Oral LD50 Rat 3,280 mg/kg Inhalation LC50 Rat 18.00 G/M3 Dermal LD50 Rabbit > 3,160.00 mg/kg
Aliphatic petroleum distillate	Inhalation LC50 Rat > 5.20 mg/l
Xylene	Oral LD50 Rat 4,300 mg/kg

SAFETY DATA SHEET

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation :No irritation hazard in normal industrial use.

Respiratory / skin sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: Contains a substance that is a probable reproductive hazard based on human studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Lungs Kidneys Liver Blood Central nervous system

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Lung disease, Liver disease, Kidney disease, Blood disorders (like anemia)

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW:	No ecological information available for this product.
MOBILITY:	No data available.
PERSISTENCE:	No data available.
BIOACCUMULATION:	No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Aromatic petroleum distillate	Acute Toxicity (Fish): LC50 96 h Oncorhynchus mykiss 9.22 mg/L (IUCLID) Acute Toxicity (Daphnia): EC50 48 h Daphnia magna 6.14 mg/L (IUCLID) Acute Toxicity (Algae): Not established
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.1 mg/L [flow-through] Acute Toxicity (Daphnia): Not established Acute Toxicity (Algae): Not established
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.1 mg/L [flow-through] Acute Toxicity (Daphnia): Not established Acute Toxicity (Algae): Not established
Aromatic petroleum distillate	Acute Toxicity (Fish): LC50 96 h Oncorhynchus mykiss 9.22 mg/L (IUCLID) Acute Toxicity (Daphnia): EC50 48 h Daphnia magna 6.14 mg/L (IUCLID) Acute Toxicity (Algae): Not established
Trimethylbenzene, 1,2,4-	Acute Toxicity (Fish): LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L [flow-through] (EPA) Acute Toxicity (Daphnia): EC50 48 h Daphnia magna 6.14 mg/L (IUCLID) Acute Toxicity (Algae): Not established
Aliphatic petroleum distillate	Acute Toxicity (Fish): LC50 96 h Pimephales promelas 45 mg/L [flow-through] (IUCLID); LC50 96 h Lepomis macrochirus 2.2 mg/L [static] (EPA); LC50 96 h Oncorhynchus mykiss 2.4 mg/L [static] (EPA) Acute Toxicity (Daphnia): Not established Acute Toxicity (Algae): Not established
Xylene	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L [flow-

SAFETY DATA SHEET

	through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53 - 29.97 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 30.26 - 40.75 mg/L [static] Acute Toxicity (Daphnia): EC50 48 h water flea 3.82 mg/L; LC50 48 h Gammarus lacustris 0.6 mg/L Acute Toxicity (Algae): Not established
--	--

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Xylenes (o-, m-, p- isomers) ethylbenzene

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT: UN1133, ADHESIVES, 3, III
IATA: UN1133, ADHESIVES, 3, III
IMDG: UN1133, ADHESIVES, 3, III, MARINE POLLUTANT (C-14-C17 CHLORINATED PARAFFIN), FLASH POINT 43°C C.C., EMS F-E, S-D

SECTION 15: REGULATORY INFORMATION**INVENTORY STATUS**

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

FEDERAL REPORTING

SAFETY DATA SHEET

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Zinc compounds	1314-13-2	1 - 5
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Xylene (mixed isomers)	1330-20-7	1 - 5
Antimony compounds	1309-64-4	0.1 - 1
ethylbenzene	100-41-4	0.1 - 1

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Quartz (Carcinogen)	14808-60-7	0.1 - 1
Titanium dioxide (Carcinogen)	13463-67-7	0.1 - 1
Antimony(III) oxide (Carcinogen)	1309-64-4	0.1 - 1
ethylbenzene (Carcinogen)	100-41-4	0.1 - 1

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 04-15-2020

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 2 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction

SAFETY DATA SHEET

Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.