

NEW



502 & 503

100% RTV Silicone



Introducing Design Polymeric DP 502 100% RTV Silicone and DP 503 100% High Temperature RTV Silicone, recommended on a variety of HVAC substrates including galvanized steel, stainless steel, aluminum, wood, fiberglass PVC, PVS, and painted substrates.

- **LEED V4** Qualified
- Non-Slump, Non-sag
- Mold and Mildew Resistant
- Low VOC
- Weather and UV Resistant
- Flexible, will not shrink or crack
- Indoor and Outdoor Usage

Meets or Exceeds:

- ASTM C920 Type S, Grade NS, Class 25
- ASTM G26
- TT-S 001543A, TT-S 00230C Type II
- FDA Regulation No. 21 CFR177 2600
- NSF Standard 51
- UL Recognized
- MIL-46106 TYPE 1

DP 502: Service temperature -50°F to 500°F.
Intermittent temperatures up to 500°F.

Packaging: 10 ounce tubes, 12 tubes per case

DP 503 Red: Service temperature -50°F to 500°F.
Intermittent temperature up to 600°F.



A Meridian Adhesives Group Company

3301 W. Segerstrom Ave.
Santa Ana, CA 92704
Toll Free 800.641.0808
Phone 714.432.0600
Fax 714.432.0660
www.designpoly.com