



Build with Proven Coatings  
Commercial + Residential

## No-Burn® Plus Spray Seal™ Over OSB & Wood Exterior WRB/Air Barrier



- Air Barrier Protection and Water-Resistive Barrier Protection.
- Listed for 1-hr/2-hr wall assemblies; simplify specs for multifamily, hotels, student housing.
- Durability against UV/Weather – 6 Months.
- ZERO Lot Line – 1-Hour Rating.
- WUI Fire Protection & FRTw Equivalent.

Tight, durable, code-compliant envelopes



## No-Burn® ThB Spray Seal™ over SPF Thermal/Ignition Barrier + Vapor Barrier

- Alternative Thermal & Ignition Barrier over approved open-cell or closed-cell SPF.
- Class II Vapor Retarder in IECC Climate Zones Marine 4–8 — ThB Spray Seal used as a Class II vapor retarder with open-cell SPF in cold/marine zones.
- For use in: Attics, Crawlspace, Walls, Basements.
- Approved for use in NFPA 285-tested exterior wall assemblies incorporating ThB Spray Seal and SPF, for Types I–IV construction, when installed as part of the tested and approved assembly configuration.



800-989-8577

[noburn.com](http://noburn.com)

[info@noburn.com](mailto:info@noburn.com)